

5 4 3 2 1

RoHS compliant **Pb Lead-free** (XX) 标注为重点管控尺寸

◆ 技术参数/Technical parameters

- 符合规范/Accord With Norm :EIA-364C
- 额定电流/Current Rating :1.5AMP
- 绝缘阻抗/Insulator Resistance :1000MΩ Min.
- 接触阻抗/Contact Resistance :20mΩ Max.
- 耐电压值/Voltage Resistance :AC 500V
- 工作温度/Operating Temperature :-40°C To +105°C
- 金属材料/Metallic Material :COPPER ALLOY
- 金属处理/Metal Treatment :Ni(30u"~50u") + Au(0.5u"~0.8u")
- 绝缘材料/Insulator Material :LCP, WHITE, UL94V-0
- 耐焊接热/Resistance To Soldering Heat :260° C ±5° C 10S MAX

TOLERANCE: ±0.05,
RECOMMENDED PCB LAYOUT
(TOP VIEW)

剖面 A-A

| | | | | | |
|-------|-------|-------|-------|---------|------------------|
| 52.10 | 50.60 | 52.40 | 48.00 | 2x25Pin | BTP200-220-003 |
| 42.10 | 40.60 | 42.40 | 38.00 | 2x20Pin | BTP200-220-003 |
| 34.10 | 32.60 | 34.40 | 30.00 | 2x16Pin | BTP200-216-003 |
| DIM D | DIM C | DIM B | DIM A | PIN No. | PART NUMBER (料号) |

THIS DRAWING IS A CONTROLLED DOCUMENT.
(此图为宇亮公司受控文件)

DIMENSIONS: (单位) mm

TOLERANCES UNLESS OTHERWISE SPECIFIED: (自由公差参照)

| | |
|-------|--------|
| 0 PLC | ± 0.20 |
| 1 PLC | ± 0.15 |
| 2 PLC | ± 0.10 |
| 3 PLC | ± 0.05 |
| 4 PLC | ± - |

ANGLES (角度公差) ± 3°

THIRD ANGLE PROJECTION (第三视角)

| | | | | |
|----------------|----------------------|------------|----------|-----------|
| A | RELEASED | 2016\11\20 | AW | WK |
| LTR (版本) | DESCRIPTION (变更内容描述) | DATE (日期) | DWN (绘图) | APVD (核准) |
| REVISIONS (修订) | | | | |

DWN (绘图) 2016\11\20
A. WU

CHEK (审核) 2016\11\20
S. CHIEN

APVD (核准) 2016\11\20
Abel

PRODUCT SPEC (产品规范)

WEIGHT (产品重量)

ASSMBLE DRAWING (组装图)

SCALE (比例) 1 : 1

SHEET (页码) 1 OF 1

东莞市宇亮电子有限公司
DONG GUAN YU LIANG ELECTRONICS CO., LTD

NAME (品名)
2.0 mm 间距,板对板 H=10.35 无防呆插头.

SIZE (尺寸) A4

DRAWING No. (图号)
P = 2041008

TEL:0769-83710858 FAX:0769-83710918 Http://www.dgyuliang.com