


DIM A	DIM B
2.05	5.00
CUSTOM	CUSTOM

PH080-2XX-XXX



产品规范 PRODUCT SPECIFICATION

1. 绝缘材质 INSULATOR MATERIAL : POLYESTER, UL94V-0 .
2. 端子材质 TERMINAL MATERIAL : COPPER ALLOY .
3. 端子电镀 FINISH : GOLD OR TIN PLATED.
4. 额定电流 CURRENT RATING : 1 AMPERE.
5. 绝缘阻抗 INSULATION RESISTANCE : 1000M OHMS MIN.
6. 耐电压 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V /1 MINUTE.
7. 接触阻抗 CONTACT RESISTANCE : 初期 Initial : 20 m Ohm Max. ;
测试后 Final : 40 m Ohm Max. .
8. 操作温度范围 OPERATING TEMPERATURE : - 40°C to +105°C.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN 08Jan2016	东莞市宇亮电子有限公司 DONG GUAN YU LIANG ELECTRONICS CO.,LTD	
		CHEK 08Jan2016		
		APVD Abel 08Jan2016	NAME PH0. 80*1. 20 DUAL ROW SMT TYPE	
		PRODUCT SPEC —	SIZE A4	DRAWING No. YL-ED-XXX
		WEIGHT —	SCALE 1 : 1 SHEET 1 of 1	
THIRD ANGLE PROJECTION		CUSTOMER DRAWING		

TOLERANCES UNLESS OTHERWISE SPECIFIED:	
0 PLC	± 0.50
1 PLC	± 0.30
2 PLC	± 0.20
3 PLC	± 0.15
4 PLC	± -
ANGLES	± 3'