

5 4 3 2 1

REVISIONS				
LTR	DESCRIPTION	DATE	DWN	APVD
A	RELEASED	01Jan16	AW	WK

NOTES:

- ELECTRICAL CHARACTERISTICS:
 - 1-1. CURRENT RATING: 0.5 Amp. MAX.
 - 1-2. VOLTAGE: 100V DC. MAX.
 - 1-3. LOW LEVEL CONTACT RESISTANCE: 100 mOhms MAX. INITIALLY.
 - 1-4. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC MIN. FOR 1 MINUTE.
 - 1-5. INSULATION RESISTANCE: (INITIAL) 1000MOhms MIN.. (FINAL) 100MOhms MIN.

BY APPLYING 500V DC ON MATED AND UNMATED CONNECTORS THROUGH MIL-STD-202, METHOD 302.
- MECHANICAL CHARACTERISTICS:
 - 2-1. DURABILITY: 5000 CYCLES.
 - 2-2. OPERATING TEMP. RANGE: -25°C TO 85°C. [INCLUDING TERMINAL TEMP. RISE]
 - 2-3. STORAGE TEMP.: -40°C TO 85°C.
- QUANTITY OF PRODUCTS: 1400PCS/REEL

NO.	PART NAME	Q'TY	DESCRIPTION	NOTE
⑥	TERMINAL	6	COPPER ALLOY	GOLD PLATING
⑤	HOUSING	1	THERMAL PLASTIC	
④	SLIDER	1	THERMAL PLASTIC	
③	SPRING	1	SUS	
②	CAM FOLLOWER	1	SUS	
①	SHELL	1	SUS	Ni PLATING

YL004-010-XXX
PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN A. WU 01Jan2016	东莞市宇亮电子有限公司 DONG GUAN YU LIANG ELECTRONICS CO.,LTD	
DIMENSIONS: mm		CHEK S. CHIEN 01Jan2016		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD Abel 01Jan2016	MICRO SIM CARD 6P PUSH PUSH SMT H=1.35MM 圆孔	
0 PLC ± 0.50 1 PLC ± 0.30 2 PLC ± 0.20 3 PLC ± 0.15 4 PLC ± - ANGLES ± 3°		PRODUCT SPEC — WEIGHT —		
THIRD ANGLE PROJECTION		CUSTOMER DRAWING	SIZE A4	DRAWING No. YL004-010
		SCALE 1 : 1	SHEET 1 of 1	

科技 . 链接 . 未来

TEL:0769-83710858 FAX:0769-83710918 Http://www.dgyuliang.com